



通用技术新兴厦门进出口
GENERTEC XINXING XIAMEN IMPORT AND EXPORT

CHINA XINXING XIAMEN IMPORT AND EXPORT CO., LTD.

ADD: 11/FL, ZHENXING BLDG, HUBIN ROAD N. XIAMEN CHINA

TEL:0592-5052128 MOBIL

E: +86 13003920231

E-MAIL: XINXINGXM03@CXXM-IEC.COM.CN

WEBSITE:

[HTTPS://CHINAMILITARYSUPPLIER.COM/](https://chinamilitarysupplier.com/)

[HTTPS://TOPMILITARYSUPPLIER.COM/](https://topmilitarysupplier.com/)



SPECIAL VEHICLE

CHINA XINXING XIAMEN IMP.& EXP. CO., LTD.

CHINA DEFENCE



Military vehicles-Armoured

APC-Gila



Armoured personnel carrier 4*4

Chassis: DongFeng 2120 4x4
Engine: Turbocharged diesel engine, 210 horsepower, 700 Nm
Length width height: 7025mm -2640-3220mm
Wheelbase: 3700 millimeters Tire/Wheel
Hub: Triangle brand, size 365/80R20
Turning radius: 9 meters
Total weight (GVW): 12000 kilograms
Load: 2500 kilograms
Range: 600 kilometers (375 miles)
Number of seats: 14
Bulletproof level:NATO Level1

APC-Tiger



Armoured personnel carrier 4*4

Engine: Cummins ISDE200-30147 kW.
Maximum speed: 125 km/h.
Dimensions: 5360mm x 2320mm x 2300mm (length x width x height).
Full load total mass: 6500 kilograms.
Vertical obstacle crossing: ≥ 350 millimeters.
Curb weight: 4700 kilograms.
Carrying capacity: 1800 kilograms.
Fuel tank capacity: 120 liters.
Crew capacity: 2+9 people.
Protective performance: Resist Type 53 7.62mm standard bullet shooting

APC-Wolf



Armoured personnel carrier 4*4

Engine: Electronic fuel injection, water-cooled, inline four cylinder, diesel engine.
Displacement: 4500 cubic centimeters (cc).
Engine power: 200 horsepower (HP)/147 kilowatts (KW).
Transmission: manual or automatic (optional).
Passengers: 2+5 people.
Combat quality: 5.6 tons (T).
Driving range: 600 kilometers (km).
Maximum speed: 115 kilometers per hour (km/h).
Fuel tank capacity: 120 liters (L).
Protective performance:Resist Type 53 7.62mm standard bullet shooting

APC-2060MCT3



Lightweight Armour Personnel carrier

Engine: Electronic fuel injection, water-cooled, inline four cylinder, diesel engine.
Displacement: 4500 cubic centimeters (cc).
Engine power: 200 horsepower (HP)/147 kilowatts (KW).
Transmission: manual or automatic (optional).
Passengers: 2+5 people.
Combat quality: 5.6 tons (T).
Driving range: 600 kilometers (km).
Maximum speed: 115 kilometers per hour (km/h).
Fuel tank capacity: 120 liters (L).
Bulletproof level:B6 NATO 4569 Standard Level 2



通用技术新兴厦门进出口
GENERTEC XINXING XIAMEN IMPORT AND EXPORT

Military vehicles-Armoured

Mine resistant-2050B



Mine resistant personnel carrier

Number of passengers: 4 people
Drive form: 4X4
Maximum total mass: 5000 kilograms (kg)
Loading weight: 1500 kilograms (kg)
Traction weight: 2000 kilograms (kg)
Total length: 4700 millimeters (mm)
Total width: 2220 millimeters (mm)
Total height: 2100 millimeters (mm)
Wheelbase: 3300 millimeters (mm)
Maximum speed: 105 kilometers per hour (km/h)
Fuel type: diesel
Highway driving distance: 2600 kilometers (km)

Bulletproof level:B6

Mine resistant-CS/VP144



Mine resistant personnel carrier

Vehicle length (millimeters): not exceeding 7100mm
Vehicle width (millimeters): not exceeding 2600mm
Vehicle height (millimeters): The height of the base model shall not exceed 2800mm
Departure angle (degrees): not less than 32 °
Width across trench (mm): 750mm
Total load capacity (kg): not exceeding 13500kg
Empty weight (kg): not exceeding 11500kg
Maximum speed (km/h): not less than 105km/h
Acceleration performance (0-60 km/h acceleration time, seconds): not exceeding 23 seconds
Maximum climbing ability (percentage): 60%
Maximum highway mileage (kilometers): not less than 700km

Bulletproof level:NATO 4569 Standard Level 2
Mine protection: higher than NATO 4569 4B protection standard

APC-2060MCT3



Mine resistant personnel carrier

Chassis: HOWO 4*4 mine resistant
Size: 7755 mm *2660 mm * 2627 mm
Min. Turning Diameter: ≤18m
Ground Clearance: 400 mm (lowest point of the axle)
Vertical Obstacle: 350 mm
Max. speed: 105 km/h(highway/instantaneous)
Seat: 1+1+10
Weight: 15000 kg

Bulletproof level:B6 NATO 4569 Standard Level 2

APC-A7



Armoured personnel carrier 6*6

Vehicle length: 6930 millimeters (mm)
Vehicle width: 2450 millimeters (mm)
Vehicle height: 2485 millimeters (mm)
Total combat weight: 15000 kilograms (kg)
Loading weight: 3000 kilograms (kg)
Curb weight: 12000 kilograms (kg)
Traction weight: 3000 kilograms (kg)
Passenger: 12 people
Drive type: 6X6
Engine power: 200 kW (km)
Top speed: 120 kilometers per hour (km/h)

Bulletproof level:B6



Military vehicles-Armoured

Armoured Patrol Bus



Border Patrol Bus

Engine model: WD615.71Q-1
Rated power: 191 kilowatts (kw)
Drive form: 6X6
Vehicle weight: 10650 kilograms (kg)
Loading weight for outdoor driving: 5000 kilograms (kg)
Dimensions (length x width x height): 8425mm x 2560mm x 3255mm (mm)
Top speed: 85 kilometers per hour (km/h)
Water wading depth: 1.2 meters (m)
Number of passengers: 19 people
Protective performance:Resist Type 53 7.62mm standard bullet shooting

Armoured Patrol Bus



Patrol bus

Chassis: Dongfeng Off road 4*4
Crew capacity: 23-27 people
Wheelbase: 3800mm
Size:7100*2500*3300mm
Weight: 14000kg
Max. Speed: 120km/h
Rated power/rpm: 221Kw/2500r/min
Approach angle: 30
Departure angle: 25
Bulletproof level: BR 6 of EU EN1522/1063

Armoured truck



Armoured Truck personnel carrier

Dimensions: 9400mm x 2590mm x 3250mm (including grating, excluding ladder)
Internal dimensions of the cargo box: 6200*2500*800mm
Wheelbase: 4500mm+1400mm
Allowable capacity: 3 people
Curb weight: 11300kg
Maximum allowable total mass: 29000kg
Maximum speed: 90km/h
Minimum stable speed: 2.5km/h
Maximum wading depth: 1000mm
Fuel consumption per 100 kilometers under limited conditions: less than 22L
Fuel tank capacity: 280L
Maximum range: 800km
Bulletproof level:EN1063-2000 (B6) level,STANAG4569 level 1 bulletproof standards

Armoured water truck



Armoured water truck (6 × 6)

Dimensions: 8400mm x 2480mm x 3200mm
Wheelbase: 3700mm+1400mm
Front/Rear Suspension: 1350mm/1950mm
Track width (front/center/rear): 2116mm/1997mm/1997mm
Approach/departure angle: 35 °/24 °
Allowable capacity: 3 people
Curb weight: 12500kg
Maximum allowable total weight of the original disc: 27000 kg
Maximum allowable axle load: front axle 7000kg, rear axle 10000kg+10000kg
Displacement: 8.3L
Maximum speed: 90km/h
Bulletproof level:EN1063-2000 (B6) level,STANAG4569 level 1 bulletproof standards



通用技术新兴厦门进出口
GENERTEC XINXING XIAMEN IMPORT AND EXPORT

Military vehicles-Troop carrier

Troop carrier-off road



Lightweight Personnel carrier
Number of passengers: 4 people
Drive form: 4X4
Maximum total mass: 5000 kilograms (kg)
Loading weight: 1500 kilograms (kg)
Traction weight: 2000 kilograms (kg)
Size: 4700*2220*2100mm
Wheelbase: 3300 millimeters (mm)
Maximum speed: 105(km/h)
Fuel type: diesel
Highway driving distance: 2600 kilometers (km)

Troop carrier-off road



Troop Carrier-Dongfeng

Chassis: BAW
Engine: 2.4T gasoline engine
Size: 4490*1825*1950mm
Wheelbase: 2600mm
With air conditioning, 4 doors and 5 seats, non-carrying body, time-sharing four-wheel drive, front coil spring and rear leaf spring, 6MT, remote control key, central lock
Max: speed: 125km/h
Minimum ground clearance (mm): 225mm
Approach angle: 42
Departure angle: 33

Troop carrier -Pick-up



Military pick-up
Number of passengers: 10 people
Drive form: 4X4
Maximum total mass: 5000 kilograms (kg)
Loading weight: 1500 kilograms (kg)
Total length: 4700 millimeters (mm)
Total width: 2220 millimeters (mm)
Total height: 2500 millimeters (mm)
Wheelbase: 3300 millimeters (mm)
Maximum speed: 105 kilometers per hour (km/h)
Fuel type: diesel
Highway driving distance: 2600 kilometers (km)

Troop carrier-20 people



Military pick-up
Chassis: BJ 2022JC
Size: 4490*1825*1950mm
Wheelbase: 2600mm
Max loading capacity: 500kg
Weight: 2120kg
Max: speed: 125km/h
Minimum ground clearance (mm): 225mm
Approach angle: 42
Departure angle: 33
Longitudinal passing angle:29
Maximum vertical obstacle clearance height (mm): 35
Maximum wading depth (mm): 60



通用技术 新兴厦门进出口
GENERTEC XINXING XIAMEN IMPORT AND EXPORT

Military vehicles-Troop carrier

Troop carrier-20 people



Troop Carrier-Dongfeng

Number of cabin members: 3
Drive mode: 4X4
Maximum total weight: 13000kg
Load capacity: 6000kg
Traction weight: 10000kg
Total length: 7300mm
Total width: 2500mm
Total height: 3500mm
Wheelbase: 3800mm
Top speed: 120km/h
Fuel type: Diesel
Highway endurance mileage: 21000km

Troop carrier-30 people



Troop Carrier-Dongfeng

Number of cabin members: 5
Drive mode: 6 × 6
Maximum total weight: 11250kg
Load capacity: 3500kg
Traction weight: 4800kg
Total length: 7600mm
Total width: 2500mm
Total height: 3000mm
Wheelbase: 4100mm+1250mm
Top speed: 90km/h
Fuel type: diesel
Highway range: 2750km

Troop carrier-20 people



Troop carrier-HOWO

Total weight: 14000kg
Engine brand: SINOTRUCK
Engine model: D10.31-50 EURO 5
Maximum output: 310HP
Transmission: HW15710C (10 forward gears, 2 reverse gears, no PTO)
Driver's cab (right-hand drive): HW76 single sleep with air conditioning
Maximum speed: 90 km/h
Wheelbase: 4300 mm
Front axle: STR
Rear axle: ST16
Body: 5000X2400X600, Floor 4mm, Side/Rear 3mm
Water wading depth: ≥ 1.2m
Fuel tank capacity: 400L
Estimated total size: 7690X2550X3500mm

Troop carrier-20 people



Personnel carrier-SHANCMAN

Total weight: 15500kg
Engine brand: SHANXI AUTOMATIC
Max. Gradeability: 60%
Gear box: RT-11509C; 9 Forward & 1 Reverse
Maximum output: 310HP
Transmission: HW15710C (10 forward gears, 2 reverse gears, no PTO)
Driver's cab (right-hand drive): HW76 single sleeper with air conditioning
Maximum speed: 85 km/h
Wheelbase: 4200 mm
Body: 7740×2500×3113mm
Fuel tank capacity: 280L
Estimated total size: 7690X2550X3500mm



Military logistics vehicles

Water tank



Water Tank

The Water Tank provide the best back-up for military, it is able to transport water, drinking water, discharge water and emergency fire function.

Drive mode: 4*2
Payload: 5ton
Size: 6030*1980*2390mm
Chassis: Dongfeng.
Power: 95hp
Wheelbase: 3300
Tank material: 5mm high tensile carbon steel

Fuel Tank



Fuel Tank

Made of Dongfeng chassis, 6X6 drive, Cummins 190 horsepower, 6-speed gearbox. Fuel Tank capacity can be 10-20 ton, the tank is made of carbon steel plate, the plate thickness is 5.2MM. it is able to support the soldier during the training.

Total weight: 10675kg
Engine brand: Dongfeng EQ6BT5.9
Wheelbase: 3640mm
Fuel tank capacity: 400L
Estimated total size: 7760*2470*2740mm

Rescue Vehicle



Protective heavy-duty rescue vehicle (6 × 6)

The vehicle can provide rapid rescue capabilities for the military. The arm behind it can rotate 360 degrees and extend 9.6 meters, lifting 16 tons.

Dimensions: 8400mm x 2480mm x 3860mm (including arm height)
Container length: 4600mm
Allowable capacity: 3 people
Curb weight: 14000kg
Maximum allowable total mass of chassis: 29000kg
Maximum allowable axle load: front axle 9000kg, rear axle 10000kg+10000kg
Maximum speed: 90km/h
Minimum stable speed: 2.5km/h
Maximum climbing gradient: 60%

Water purification truck



Water purification truck

The vehicle is equipped with a variety of water purification systems, suitable for military field training, border defense forces, etc., and can purify 4 tons of pure water per hour.

Total weight: 8200kg
Curb weight: 8005kg
Dimensions: 7100mm × 2550mm × 2950mm
Engine model: YCY30165-60
Engine horsepower: 165
Wheelbase: 3800mm
Tire specification: 245/70R19.5



通用技术新兴厦门进出口
GENERTEC XINXING XIAMEN IMPORT AND EXPORT

Military logistics vehicles

Mobile Kitchen Trailer



Mobile Kitchen trailer

Overall Weight: 1850 Kg
Min. Terrain clearance: 340 mm
Wheelbase: 1990 mm
Departure angle: 25°
Fording depth: 500 mm
Overall dimension: 4000×2250×2420 mm
Performance:
(1) Suitable for boiling, roasting, frying western food
(2) 4 cookers working together to supply dishes for 250 persons within 2 hours
(3) Diesel or natural gas is used for the stove

Mobile Kitchen



Mobile Kitchen

The vehicle has cooking functions such as steaming, boiling, frying and stir-frying, and can process 300 servings of food per hour. It is equipped with a 1000L capacity thermal water tank. And it has a car refrigerator to store fresh food.
Chassis: HOWO 6*6
Wheelbase: 5200 + 1400mm
Emission: 9726ml
Horse power: 280hp

Shower Vehicle



Shower vehicle

This vehicle can accommodate 36 people/h (10 minutes per person), with comfortable shower environment and complete sanitary
Chassis: HOWO
Dimensions: 10330*2550*3980mm
Drive model: 4*2
Allowable capacity: 2 people
Weight: 18000kg
Max speed: 100km/h
Front Axle/back axle: 1430/2800
Equipment: shower area, cloth changing area, water boiling area

Laundry Vehicle



Laundry Vehicle

The vehicle is mainly used for washing clothes in the field. The main special equipment is a dryer, washing machine, storage rack, etc. The side protection material of the vehicle is aluminum alloy 6061-T6, and is bolted.
Chassis: HOWO 4*2
Size: 10470*8500*X2510mm
Weight: 16200kg
Highest speed: 90km/h



通用技术新兴厦门进出口
GENERTEC XINXING XIAMEN IMPORT AND EXPORT

Police vehicles-APC

APC-WONSIR



Armoured personnel carrier
Model :GDJ5063XFB(4X4)
Weight:5510kg
Size:5645mmX2220X2990mm
Diesel engine,3.0L/L4/170KW
Transmission:8-speed Electric Automatic
Number of Passenger:4-9 persons
Maximum Speed:130km/h
Braking:ABS;
Front/Disk:Rear/Disk/ABS
Bulletproof level:FB4 According To EN1522 standard

APC-SMILODON



Armoured personnel carrier
Model:GDj5091XFB(4X4)
Size:6545mmX2415X3020mm
Engine:EFI Gasoline Engine 7.3L/V8/257KW
GVWR:8165kg
Transmission:10-speed Electric Automatic
Number of Passenger:2+2+6 persons
Maximum Speed:130km/h
Braking:ABS;
Front/Disk:Rear/Disk/ABS
Bulletproof level:FB4 According To EN1522 standard

APC-SPINOSAURUS



Armoured personnel carrier
Model:GDj5097XFB(4X4)
Size:7130mmX2450X3060mm
Engine:Heavy duty HEMI Engine
6.4L/V8/272KW
GVWR:8619kg
Transmission:6-speed Electric Automatic
Number of Passenger:2+2+2 persons
Maximum Speed:130km/h
Braking:ABS;
Front/Disk:Rear/Disk/ABS
Protection level:Six Sides FB4According To EN1522 standard
Maximum db:>151dB
Effective range:>100m
Sound transmission distance:>1km
Firepower coverage:30mX40mMaximum Range:130m
Bulletproof level:FB4 According To EN1522 standard

APC-WOLF



Armoured personnel carrier
Model:GDj5045XFB(4X4)
GVWR:4495kg
Size:5505mmX2190X2295mm
Engine:Heavy duty HEMI Engine,6.4L/V8/301KW.
Transmission:6-speed Electric Automatic
Number of Passenger:2+2+3 persons
Maximum Speed:140km/h
Braking:ABS;
Front/Disk:Rear/Disk/ABS
Bulletproof level:FB4 According To EN1522 standard



通用技术 新兴厦门进出口
GENERTEC XINXING XIAMEN IMPORT AND EXPORT

Police Special vehicles

Personnel carrier-Ford



Police personnel carrier
Model:GDj5042TXU
GVWR:3510kg
Size:5550mmX2040X2665mm
Engine:DURATORQ4D20C6H
Diesel Engine 2.0L/105kw
Number of Passenger:4-9 persons
Maximum speed:160km/h
Wheelbase:3300mm

Personnel carrier-IVECO



Armoured personnel carrier
Model :GDj5043TXU
Size:5690mmX2035X2860mm
Engine:S0FIM8140.47Z6
Diesel Engine 2.5L/90KW
GVWR:3750kg
Number of Passenger:5-8 persons
Maximum Speed:125km/h
Wheelbase:3310mm

Road Barrier Vehicle



Road Carrier vehicle
Model:GDj5070CBZ
Size:7030mmX2300X3000mm
Engine:Turbo Diesel Engine 5.2L/139KW
GVWR:7360kg
Transmission:6-speed Electric Automatic
Number of Passenger:3 persons
Maximum Speed:110km/h
Number of Barricade:40pcs
Weight of Barricade:55kg
Length when Barricades join together:56m
Barricade size:1400x2100x40mm

Road block vehicle



Road block vehicle
Drive mode: 4x2
Total weight: 13000kg
Dimensions: 8052mm × 2300mm × 3850mm
Maximum speed on the highway: 90 km/h
Mesh size of road drop board unit: 12m
Unfolding size of road drop board: 9330mm × 3110mm
Road descent board deployment time: no more than 90 seconds
The maximum thrust that the front of the road drop plate can withstand: 1.5 tons
Engine brand and model: 1015.20
Maximum rated power and speed: 193 horsepower



通用技术 新兴厦门进出口
GENERTEC XINXING XIAMEN IMPORT AND EXPORT

Police Special vehicles

Water cannon-10ton



Water cannon vehicle 3 water guns

Carrying capacity: 2+4 people
Chassis: Sinotruck 6*4
Size: 10200*2550*3860 mm
Capacity: 10ton
Weight:25000kg
Water shooting range: 65m
Water gun rotating angle:
-single:-135~135
-double:-135~5
Max speed: 100km/h

Water cannon-10ton



Water Cannon vehicle

Carrying capacity: 2+4 people
Chassis: Sinotruck 6*4
Size: 9940*3950*2496
Capacity: 10ton
Weight:25000kg
Water shooting range: 65m
Water gun rotating angle:
-single:-135~135
-double:-135~5
Max speed: 100km/h

Water cannon-armoured cabin



Water cannon vehicle 3 water guns

Carrying capacity: 2+4 people
Chassis: Sinotruck 6*4
Size: 10350*2496*950mm
Capacity: 10ton
Weight:25000kg
Water shooting range: 65m
Water gun rotating angle:
-single:-135~135
-double:-135~5
Max speed: 100km/h
Carbin: armoured, with shooting point

Water cannon-6ton



Water Cannon vehicle

Carrying capacity: 2 people
Chassis: Sinotruck 4*2
Size: 8300*3650*2500mm
Capacity: 6ton
Weight: 16200kg
Water shooting range: 65m
Water gun rotating angle:
-single:-135~135
-double:-135~5
Max speed: 89km/h



通用技术 新兴厦门进出口
GENERTEC XINXING XIAMEN IMPORT AND EXPORT

Other vehicles-fire fighting vehicles

GT-FF01



Fire fighting vehicle

Chassis brand and model: Ford F550
Dimensions (length x width x height):
7300mm x 2550mm x 2900mm
Fire extinguishing agent capacity:
Water: 1500kg
Class A foam: 200kg
Drive system: 4x2
Number of seats (people): 5

GT-FF02



Fire fighting vehicle

Power (kw/r/min): 81/2200rpm
Tire type: 315/70R15
Fuel tank capacity (L): 200
Battery capacity (Ah): 100
Maximum traction force (kN): 60kN (100kN when adding counterweight to 12 tons)
Note: When driving on asphalt or cement roads, the traction coefficient $\mu=0.8$
Maximum towing weight (kg): 90000kg (120 tons after adding counterweight)
Curb weight (kg): 9000kg (12 tons after adding counterweight)

GT-FF03



**Fire fighting vehicle-
FOAM+WATER**

Chassis: IVECO Hongyan 6*4
Size: 10030*2800*3950mm
Weight: 27000kg
Emission: 8709 ml
Flow Rate: 80 L/s at 1.0MPa (Normal Pressure)
Capacity of Extinguishing Agent: Water 8000L + Foam 1000L

GT-FF04



**Fire fighting vehicle-
FOAM+WATER**

Chassis: IVECO Hongyan 6*4
Size: 9680*2550*3620mm
Weight: 27600kg
Highest speed: 100Km/h
Flow Rate: 60L/S 1.0MPa
Capacity of Extinguishing Agent: Water 9100L + Foam 3040L



通用技术 新兴厦门进出口
GENERTEC XINXING XIAMEN IMPORT AND EXPORT

Other vehicles-communication vehicle

GT-CM01



Emergency communication car
Chassis brand and model: pickup truck or SUV
Boundary dimensions (length x width x height) (mm): (5000-6000) × 2043 × 2330
Total mass (T): 2.5-3.5
Number of on-site staff (person): 2-5
Vehicle wheelbase (mm): 2800-3300
Rated power of engine (kw): 3.5-7.5

GT-CM02



Emergency communication car
Engine: Cummins ISDE200-30147 kW.
Maximum speed: 125 km/h.
Dimensions: 5360mm x 2320mm x 2300mm (length x width x height).
Full load total mass: 6500 kilograms.
Vertical obstacle crossing: ≥ 350 millimeters.
Curb weight: 4700 kilograms.
Carrying capacity: 1800 kilograms.
Fuel tank capacity: 120 liters.
Crew capacity: 2+9 people.
Protective performance: The front of the vehicle can withstand Type 53 7.62mm armor piercing bullets at a distance of 100 meters; The side and rear of the vehicle can withstand Type 53 7.62mm standard bullets at a distance of 100 meters.

GT-CM03



Emergency communication car
Raider Buggy
Boundary dimensions (length x width) (mm): 4000 × 2300
Wheelbase (mm): 2600
Engine power (kw): 10
Mast lifting height (m): 15
Empty weight (t): 1.3

GT-CM05



Emergency communication car
Chassis model: Large truck or tractor
Boundary dimensions (length x width x height) (mm): (10000-12000) × 2500 (unfolded 4500) × 3990
Total mass (T): 16-26
Number of on-site staff (person): 11-30
Rated power of engine (kw): 5-25

Other vehicles-ambulance

FOTON-G9



Ambulance
Size: 5380×1920×2505mm
Wheelbase: 3110mm
Weight: 3400kg
Front / rear overhang: 1190/1080(mm)
Front Suspension: Double wishbone type torsion bar spring independent suspension
With Emergency Alarm System, Air Conditioner and Heater, Power Supply and Lighting System and Patient's compartment

FOTON-4WD



Ambulance
Size: 5445×1830×2600mm
Wheelbase: 3105mm
Weight: 2910kg
Tire: 245/70R16
Front Suspension: Double wishbone type torsion bar spring independent suspension
With Emergency Alarm System, Air Conditioner and Heater, Power Supply and Lighting System and Patient's compartment

JINBEI HIACE



Ambulance
Size: 4495×1680×2150mm
Wheelbase: 2945mm
Weight: 1980kg
Tire: 195/65R15
Central control + power window MPS
With Emergency Alarm System, Air Conditioner and Heater, Power Supply and Lighting System and Patient's compartment

GT-AB05



Bulletproof level:Resist Type 53 7.62mm standard bullet shooting

Ambulance-armoured
Size: 5360mm*2320mm*2300mm
Wheelbase: 3310mm
Weight: 6500kg
Tire: 37×12.5R16.5
Bulletproof standard: It can withstand the type 53 7.62mm standard bullet at a distance of 100 meters
Included: Alarm lights: 4units/2.300w siren: 1unit/ MOTOROLA 400mb ultrashort wave: 1unit/Search lights: 1unit/ Ventilator: 1unit/Defibrillator monitor: 1unit /Oxygen tanks: 2units/First aid cabinet: 1unit/Stationary stretcher: 2units/Air conditioner : 1unit/Ventilating fan : 1unit/Internal lighting : 2units/Fire extinguishers : 2units/On-board tools: 1unit



Other vehicles-cash in transit

GT-CS01



Bulletproof level:B4

Cash in transit

Drive mode: 4x4
Boundary dimensions (length x width x height) (mm): 5560 (with front and rear bumpers) x1940x2080 (manual sunroof)
Cargo hold space dimensions (length x width x height) (mm): 1580x1580x1200
Volume (m ³): 3.0
Curb weight (kg): 2340, 2380
Total weight (kg): 2895
Rated load capacity (kg) (including passengers): 555, 515
Rated power (kw/r/min): 175/5500
Wheelbase (mm): 3110
Tire specifications: 245/70R16, 265/60R18
Protection level: B4 higher, customizable according to user needs

GT-CS02



Bulletproof level:B4

Cash in transit

Drive mode: 4 × 2
Boundary dimensions (length x width x height) (mm): 5990x2080x2140
Dimensions of cargo hold space (length x width x height) (mm): 2330 × 1720 × 1410
Volume (m ³): 5.65 (single-layer door)
Curb weight (kg):
Single layer door: 2720kg
Double layered door: 2810kg
Long body and double doors: 2900kg
Total weight (kg): 4000
Maximum power (Kw/r/min): 90/3200
Tire specification: 185/75 R16C
Protection level: B4 higher

GT-CS03



Bulletproof level:B4

Cash in transit

Engine: Electronic fuel injection, water-cooled, inline four cylinder, diesel engine.
Displacement: 4500 cubic centimeters (cc).
Engine power: 200 horsepower (HP)/147 kilowatts (KW).
Transmission: manual or automatic (optional).
Passengers: 2+5 people.
Combat quality: 5.6 tons (T).
Driving range: 600 kilometers (km).
Maximum speed: 115 kilometers per hour (km/h).
Fuel tank capacity: 120 liters (L).

GT-CS04



Bulletproof level:EN1522/1523 BR2

Cash in transit

External dimensions: 5341mm x 1885mm x 1815mm
Wheelbase: 3230mm
Number of seats: 5
Drive mode: 4x4
Displacement: 2.378 liters
Fuel type: gasoline
Power: 218 horsepower/5600 revolutions per minute
Torque: 320-350 Nm/2000 RPM
Transmission: 6-speed manual (6MT)
Emission standard: Euro V
Braking system: front disc/rear disc
Steering System: Power Steering



通用技术新兴厦门进出口
GENERTEC XINXING XIAMEN IMPORT AND EXPORT

Other vehicles-airport ground support vehicle

GT-SP01



Airport ground support vehicle

Total length x width x height:
Wide platform: 8000x3090x3680mm
Curb weight: 9500kg
Passenger elevator working height: 2150-5800mm
Number of stairs up and down: 13+14 (including tail staircase)
Stair size (DXWXH): 276x1500x192mm
Minimum stable speed: 0.36km/h
Operating temperature range: -30-60 ° C
Electricity: 81.14Kwh
Charging mode: DC fast charging: (>540V)
Charging time: ≤ 2 hours

GT-SP02



Airport ground support vehicle

Power (kw/r/min): 81/2200rpm
Tire type: 315/70R15
Fuel tank capacity (L): 200
Battery capacity (Ah): 100
Maximum traction force (kN): 60kN (100kN when adding counterweight to 12 tons)
Note: When driving on asphalt or cement roads, the traction coefficient $\mu=0.8$
Maximum towing weight (kg): 90000kg (120 tons after adding counterweight)
Curb weight (kg): 9000kg (12 tons after adding counterweight)

GT-SP03



Airport ground support vehicle

Dimensions (length x width x height):
Closed cab: 8180x2150x2150mm
Open cab: 8180x2150x1850mm
Front end lifting range of conveyor belt: 1180~4250mm
Rear end lifting range of conveyor belt: 390~1450mm
Conveyor speed: 0.16~0.5m/s
Belt width: 700mm
Conveyor belt carrying capacity: 135kg/m
Maximum speed: 40km/h
Operating temperature range: -35~60 °C
Curb weight:
Closed cab: 3850kg
Open cab: 3650kg
Range: 300km

GT-SP04



Airport ground support vehicle

Work platform height: 2200-5800mm
Vehicle rated load: 1000kg
Fixed platform rated load: 400kg
Rated load of activity platform: 300kg
Platform expansion range: 0-600mm
Fixed platform size (length x width): 2750x2270mm
Curb weight: 9150kg
Boundary dimensions (length x width x height): 7690x2680x3720mm
Engine emissions:
The emissions of pollutants comply with the requirements of Stage 6b of GB17691-2018, and the exhaust smoke level meets the Stage b-limit of GB3847-2018 Free Acceleration Method.
Vehicle dimensions (length x width x height) (interior): 4240x2400x2100mm



Other vehicles-amphibious and construction vehicles

CXXM-BV226



Model :CXXM-BV226
Curb weight:5600kg
Payload:4000kg
Gross weight:9600kg
Passengers:19(20) people
Size:7680mmX1900X2340mm
Top speed:land:67km/h;water:9.8km/h
Engine:Fiat F1CE8481K
Automatic Transmission:NJL6R40A
Displacement:2.998lcc
Engine Power:169BHP

CXXM-ET200

Model :CXXM-ET200
Total weight:20700kg
Standard bucket capacity:0.8m3
Bucket digging force:135KN
Arm digging force:80KN
Slewing speed:10r/min
Max. digging radius:9800mm
Max. digging height:11000mm
Max. unloading clearance:8000mm
Max. digging depth:6350mm
Max. travel speed:15km/h
Max. driving gradeability:25°
Max. walking gradeability:45°
Max.obstacle clearing capability:2800mm
Max. fording depth:2400mm
Max. pace:6500mm
Max. adaptive working slope:30°



CXXM BV228



Model :CXXM-BV228(8x8)
Curb weight:830kg
Payload:700kg
Gross weight:1530kg
Size:3495mmX1825X1240mm
Engine:E6 Engine 7.36/V6 350ps
Passengers:6-8 people
Driving:land:wheel;water:tire sculling
Top speed:land:60km/h;water:8km/h
Turning radius:left: 750mm;right:700mm
Engine model:SQR372
Engine displacement:800cc
Compression:9.5:1
Rated power and speed:70Nm
Fuel consumption:50Ltr/300km
Fuel:Gasoline 92 and above



CXXM-GT350J

Model :CXXM-GT350J
Size:7650mmX3400X3500mm
Chassis type:wheeled model
Boundary dimension:7650×3400×3500mm
Accommodation:80km/h
Maximum travelling speed:2
Maximum range:500km
Maximum gradability:25°
Max fording depth:1.2m
Blade width:3.4m
Maximum cutting depth:0.45m
Max.lift height:1m
Operation efficiency:160m3/h
Wireless remote control distance:50m
Working temperature:-40~ +46°
Altitude of working plateau:>4500m
Cab protection function:Anti-rollover, anti-falling objects



通用技术新兴厦门进出口
GENERTEC XINXING XIAMEN IMPORT AND EXPORT

